



DRAINAGE CATHETER-PIGTAIL TYPE



- Used for nephrostomy, abscess, and other multipurpose drainage.
- The safety string lock system provides strong fixation of the pigtail.
- Hydrophilic decreased friction of the distal catheter for easy insertion.
- Large oval drainage holes increase drainage capability.
- Supplied sterile in peel-open packages.
- Intended for one-time use.

PIGTAIL TYPE (BT-PD4-series)



With SAFETY STRING LOCK						
Order Number	Size	Accepts Guide Wire Dia.	Working Length	Order Number	Size	Accepts Guide Wire Dia.
BT-PD4-0620-W	6F	.035 inch (0.89mm)	19 cm (XX=20)	BT-PD4-1020-W	10F	.038 inch (0.97mm)
BT-PD4-0625-W	6F	.035 inch (0.89mm)	24 cm (XX=25)	BT-PD4-1025-W	10F	.038 inch (0.97mm)
BT-PD4-0630-W	6F	.035 inch (0.89mm)	29 cm (XX=30)	BT-PD4-1030-W	10F	.038 inch (0.97mm)
BT-PD4-0635-W	6F	.035 inch (0.89mm)	34 cm (XX=35)	BT-PD4-1035-W	10F	.038 inch (0.97mm)
BT-PD4-0640-W	6F	.035 inch (0.89mm)	39 cm (XX=40)	BT-PD4-1040-W	10F	.038 inch (0.97mm)
BT-PD4-0645-W	6F	.035 inch (0.89mm)	44 cm (XX=45)	BT-PD4-1045-W	10F	.038 inch (0.97mm)
BT-PD4-0650-W	6F	.035 inch (0.89mm)	49 cm (XX=50)	BT-PD4-1050-W	10F	.038 inch (0.97mm)
BT-PD4-0720-W	7F	.035 inch (0.89mm)	19 cm (XX=20)	BT-PD4-1220-W	12F	.038 inch (0.97mm)
BT-PD4-0725-W	7F	.035 inch (0.89mm)	24 cm (XX=25)	BT-PD4-1225-W	12F	.038 inch (0.97mm)
BT-PD4-0730-W	7F	.035 inch (0.89mm)	29 cm (XX=30)	BT-PD4-1230-W	12F	.038 inch (0.97mm)
BT-PD4-0735-W	7F	.035 inch (0.89mm)	34 cm (XX=35)	BT-PD4-1235-W	12F	.038 inch (0.97mm)
BT-PD4-0740-W	7F	.035 inch (0.89mm)	39 cm (XX=40)	BT-PD4-1240-W	12F	.038 inch (0.97mm)
BT-PD4-0745-W	7F	.035 inch (0.89mm)	44 cm (XX=45)	BT-PD4-1245-W	12F	.038 inch (0.97mm)
BT-PD4-0750-W	7F	.035 inch (0.89mm)	49 cm (XX=50)	BT-PD4-1250-W	12F	.038 inch (0.97mm)
BT-PD4-0820-W	8F	.038 inch (0.97mm)	19 cm (XX=20)	BT-PD4-1420-W	14F	.038 inch (0.97mm)
BT-PD4-0825-W	8F	.038 inch (0.97mm)	24 cm (XX=25)	BT-PD4-1425-W	14F	.038 inch (0.97mm)
BT-PD4-0830-W	8F	.038 inch (0.97mm)	29 cm (XX=30)	BT-PD4-1430-W	14F	.038 inch (0.97mm)
BT-PD4-0835-W	8F	.038 inch (0.97mm)	34 cm (XX=35)	BT-PD4-1435-W	14F	.038 inch (0.97mm)
BT-PD4-0840-W	8F	.038 inch (0.97mm)	39 cm (XX=40)	BT-PD4-1440-W	14F	.038 inch (0.97mm)
BT-PD4-0845-W	8F	.038 inch (0.97mm)	44 cm (XX=45)	BT-PD4-1445-W	14F	.038 inch (0.97mm)
BT-PD4-0850-W	8F	.038 inch (0.97mm)	49 cm (XX=50)	BT-PD4-1450-W	14F	.038 inch (0.97mm)
BT-PD4-0920-W	9F	.038 inch (0.97mm)	19 cm (XX=20)	BT-PD4-1620-W	16F	.038 inch (0.97mm)
BT-PD4-0925-W	9F	.038 inch (0.97mm)	24 cm (XX=25)	BT-PD4-1625-W	16F	.038 inch (0.97mm)
BT-PD4-0930-W	9F	.038 inch (0.97mm)	29 cm (XX=30)	BT-PD4-1630-W	16F	.038 inch (0.97mm)
BT-PD4-0935-W	9F	.038 inch (0.97mm)	34 cm (XX=35)	BT-PD4-1635-W	16F	.038 inch (0.97mm)
BT-PD4-0940-W	9F	.038 inch (0.97mm)	39 cm (XX=40)	BT-PD4-1640-W	16F	.038 inch (0.97mm)
BT-PD4-0945-W	9F	.038 inch (0.97mm)	44 cm (XX=45)	BT-PD4-1645-W	16F	.038 inch (0.97mm)
BT-PD4-0950-W	9F	.038 inch (0.97mm)	49 cm (XX=50)	BT-PD4-1650-W	16F	.038 inch (0.97mm)

Without SAFETY STRING LOCK						
Order Number	Size	Accepts Guide Wire Dia.	Working Length	Order Number	Size	Accepts Guide Wire Dia.
BT-PD4-0520	5F	.035 inch (0.89mm)	19 cm (XX=20)	BT-PD4-1020	10F	.038 inch (0.97mm)
BT-PD4-0525	5F	.035 inch (0.89mm)	24 cm (XX=25)	BT-PD4-1025	10F	.038 inch (0.97mm)
BT-PD4-0530	5F	.035 inch (0.89mm)	29 cm (XX=30)	BT-PD4-1030	10F	.038 inch (0.97mm)
BT-PD4-0535	5F	.035 inch (0.89mm)	34 cm (XX=35)	BT-PD4-1035	10F	.038 inch (0.97mm)
BT-PD4-0540	5F	.035 inch (0.89mm)	39 cm (XX=40)	BT-PD4-1040	10F	.038 inch (0.97mm)
BT-PD4-0545	5F	.035 inch (0.89mm)	44 cm (XX=45)	BT-PD4-1045	10F	.038 inch (0.97mm)
BT-PD4-0550	5F	.035 inch (0.89mm)	49 cm (XX=50)	BT-PD4-1050	10F	.038 inch (0.97mm)
BT-PD4-0620	6F	.035 inch (0.89mm)	19 cm (XX=20)	BT-PD4-1220	12F	.038 inch (0.97mm)
BT-PD4-0625	6F	.035 inch (0.89mm)	24 cm (XX=25)	BT-PD4-1225	12F	.038 inch (0.97mm)
BT-PD4-0630	6F	.035 inch (0.89mm)	29 cm (XX=30)	BT-PD4-1230	12F	.038 inch (0.97mm)
BT-PD4-0635	6F	.035 inch (0.89mm)	34 cm (XX=35)	BT-PD4-1235	12F	.038 inch (0.97mm)
BT-PD4-0640	6F	.035 inch (0.89mm)	39 cm (XX=40)	BT-PD4-1240	12F	.038 inch (0.97mm)
BT-PD4-0645	6F	.035 inch (0.89mm)	44 cm (XX=45)	BT-PD4-1245	12F	.038 inch (0.97mm)
BT-PD4-0650	6F	.035 inch (0.89mm)	49 cm (XX=50)	BT-PD4-1250	12F	.038 inch (0.97mm)
BT-PD4-0720	7F	.035 inch (0.89mm)	19 cm (XX=20)	BT-PD4-1420	14F	.038 inch (0.97mm)
BT-PD4-0725	7F	.035 inch (0.89mm)	24 cm (XX=25)	BT-PD4-1425	14F	.038 inch (0.97mm)
BT-PD4-0730	7F	.035 inch (0.89mm)	29 cm (XX=30)	BT-PD4-1430	14F	.038 inch (0.97mm)
BT-PD4-0735	7F	.035 inch (0.89mm)	34 cm (XX=35)	BT-PD4-1435	14F	.038 inch (0.97mm)
BT-PD4-0740	7F	.035 inch (0.89mm)	39 cm (XX=40)	BT-PD4-1440	14F	.038 inch (0.97mm)
BT-PD4-0745	7F	.035 inch (0.89mm)	44 cm (XX=45)	BT-PD4-1445	14F	.038 inch (0.97mm)
BT-PD4-0750	7F	.035 inch (0.89mm)	49 cm (XX=50)	BT-PD4-1450	14F	.038 inch (0.97mm)
BT-PD4-0820	8F	.038 inch (0.97mm)	19 cm (XX=20)	BT-PD4-1620	16F	.038 inch (0.97mm)
BT-PD4-0825	8F	.038 inch (0.97mm)	24 cm (XX=25)	BT-PD4-1625	16F	.038 inch (0.97mm)
BT-PD4-0830	8F	.038 inch (0.97mm)	29 cm (XX=30)	BT-PD4-1630	16F	.038 inch (0.97mm)
BT-PD4-0835	8F	.038 inch (0.97mm)	34 cm (XX=35)	BT-PD4-1635	16F	.038 inch (0.97mm)
BT-PD4-0840	8F	.038 inch (0.97mm)	39 cm (XX=40)	BT-PD4-1640	16F	.038 inch (0.97mm)
BT-PD4-0845	8F	.038 inch (0.97mm)	44 cm (XX=45)	BT-PD4-1645	16F	.038 inch (0.97mm)
BT-PD4-0850	8F	.038 inch (0.97mm)	49 cm (XX=50)	BT-PD4-1650	16F	.038 inch (0.97mm)
BT-PD4-0920	9F	.038 inch (0.97mm)	19 cm (XX=20)			
BT-PD4-0925	9F	.038 inch (0.97mm)	24 cm (XX=25)			
BT-PD4-0930	9F	.038 inch (0.97mm)	29 cm (XX=30)			
BT-PD4-0935	9F	.038 inch (0.97mm)	34 cm (XX=35)			
BT-PD4-0940	9F	.038 inch (0.97mm)	39 cm (XX=40)			
BT-PD4-0945	9F	.038 inch (0.97mm)	44 cm (XX=45)			
BT-PD4-0950	9F	.038 inch (0.97mm)	49 cm (XX=50)			